

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 1 of 15

1. Product and Company Identification

Product Name : MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON
Product Code : 22750F-26307-GL
Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Randolph Products Company
33 Haynes Circle
Chicopee, MA 01020

Information Phone: 413-592-4191
Emergency Phone: ChemTel 800-255-3924

2. Hazards Identification

EMERGENCY OVERVIEW

DANGER

Highly Flammable Liquid & Vapor, Category 2
Acute Toxicity, Category 4
Skin Irritation, Category 2
Eye Irritation, Category 2B

Chronic Toxicity, (Carcinogenicity) Category 2



Potential Health Effects

Eye:
Causes eye irritation.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 2 of 15

Skin:

Causes skin irritation.

Ingestion:

If swallowed, call a poison control center or physician if you feel unwell.

Rinse mouth.

Inhalation:

May cause drowsiness or dizziness.

Chronic (Cancer) Information:

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

Reproduction Information:

INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:

Dermatitis or other skin conditions.

3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
TITANIUM DIOXIDE	13463-67-7	21.060
ACGIH: 10 MG/M3 TWA		
OSHA: 10 MG/M3 TWA		
ACETONE	67-64-1	9
ACGIH TLV: 500 PPM TWA		
ACGIH TLV: 750 PPM STEL		
OSHA PEL: 1000 PPM TWA		
OSHA VPEL: 750 PPM TWA		
OSHA VPEL: 1000 PPM STEL		
SILICA GEL	63231-67-4	8
ACGIH TLV: 10 MG/M3 TWA		
OSHA PEL: 6 MG/M3 TWA		
METHYL NORMAL AMYL KETONE	110-43-0	7
OSHA PEL 100 PPM - TWA		

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 3 of 15

OSHA VPEL 100 PPM -TWA		
ACGIH TLV 50 PPM - TWA		
ACGIH TLV 233 MG/M3 - TWA		
SILICA, AMORPHOUS	68855-54-9	5
ACGIH: 10 MG/M3 TWA - TOTAL DUST		
OSHA: 20 MPPCF TWA		
METHYL ETHYL KETONE	78-93-3	3
ACGIH: 200 PPM TWA		
OSHA: 200 PPM TWA		
LT YELLOW IRON OXIDE	51274-00-1	2
ACGIH: 5 MG/M3 TWA (FUMES)		
OSHA: 10 MG/M3 TWA (FUMES)		
TERTIARY BUTYL ACETATE	540-88-5	2
ACGIH: 200 PPM TWA		
OSHA: 200 PPM TWA		
N-BUTYL ACETATE	123-86-4	1
ACGIH: 150 PPM TWA		
OSHA: 150 PPM TWA		
ACGIH: 200 PPM STEL		
OSHA: 200 PPM CEILING		
ETHYL BENZENE	100-41-4	.070
ACGIH TLV 100 PPM - TWA		
OSHA PEL 100 PPM - TWA		
OSHA PEL 100 PPM - TWA		
OSHA PEL 125 PPM - CEILING		

4. First Aid Measures

Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Ingestion:

If swallowed: Immediately call a poison center/physician.
Do NOT induce vomiting.

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison control center/get medical attention if you feel unwell.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 4 of 15

Note to Physicians:
INFORMATION NOT AVAILABLE.

5. Fire Fighting Measures

Flammable Properties:

Flash Point: -4 F Method: TCC

Explosive Limits:

Lower explosive limit: 1.0
Upper explosive limit: 12.8

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/state/federal regulations.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 5 of 15

7. Handling and Storage

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 6 of 15

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 133 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: n/a

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.405

Coating VOC: 1.86 lb/gl

Material VOC: 1.53 lb/gl

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

INFORMATION NOT AVAILABLE.

Hazardous Polymerization:

Will not occur under normal conditions.

11. Toxicological Information

Eye Irritation/Damage:

Component 100-41-4:

Mild eye irritation, Category 2b

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 7 of 15

Component 67-64-1:
Mild eye irritation, Category 2b

Component 110-43-0:
Mild eye irritation, Category 2b

Component 540-88-5:
Based on available data, the classification criteria are not met.

Skin Irritation/Damage:
Component 100-41-4:
LD50: >2000 mg/kg, rat. Category 5

Component 67-64-1:
LD50: 7426 mg/kg, rat. Category 5
Mildly irritating to skin.
Component 110-43-0:
LD50: >2000 mg/kg, rat. Category 5

Component 540-88-5:
LD50: >2000 mg/kg, rabbit. Category 5.

Acute Oral Toxicity:
Component 100-41-4:
LD50: >2000 mg/kg, rat. Category 5.

Component 13463-67-7:
LD50: 10,000 mg/kg, rat. Category 5
Component 67-64-1:
LD50: 5800 mg/kg, rat. Category 5

Component 110-43-0:
LD50: 1670 mg/kg, rat. Category 4

Component 123-86-4:
LD50: 10,700 mg/kg, rat. Category 5
Component 540-88-5:
LD50: 4,500 mg/kg, rat. Category 5

Acute Inhalation Toxicity:
Component 100-41-4:
LC50: 2-20 mg/l, rat. Category 3

Component 67-64-1:
LC50: 16000 mg/l, rat. Category 4

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 8 of 15

Component 110-43-0:

LD50: >16.7 mg/kg, rat. Category 4

Component 540-88-5:

LC50: 12.52 mg/l, rat. Category 2

Respiratory/Skin Sensitization:

Component 100-41-4:

No evidence of respiratory or skin sensitization.

Component 67-64-1:

No evidence of respiratory or skin sensitization.

Component 110-43-0:

No evidence of respiratory or skin sensitization.

Component 540-88-5:

No evidence of respiratory or skin sensitization.

Carcinogenicity:

Component 100-41-4:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 13463-67-7:

Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans). GHS Category 2.

Component 67-64-1:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 110-43-0:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Component 540-88-5:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Reproductive Toxicity:

Component 100-41-4:

No evidence of human reproductive toxicity.

Component 67-64-1:

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 9 of 15

No evidence of human reproductive toxicity.

Component 110-43-0:

No evidence of human reproductive toxicity.

Component 540-88-5:

No evidence of human reproductive toxicity.

Germ Cell Mutagenicity:

Component 100-41-4:

No data

Component 67-64-1:

No data

Component 110-43-0:

No data

Component 540-88-5:

No data

Aspiration Toxicity:

Component 100-41-4:

Not classified as an Aspiration Hazard.

Component 67-64-1:

Not classified as an Aspiration Hazard.

Component 110-43-0:

Not classified as an Aspiration Hazard.

Component 123-86-4:

Not classified as an Aspiration Hazard.

Component 540-88-5:

Not classified as an Aspiration Hazard.

STOT-single exposure

Component 100-41-4:

No data

Component 67-64-1:

No Data

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 10 of 15

Component 110-43-0:

No data

Component 123-86-4:

No data Component 540-88-5:

Transient target organ effects (Category 3);

Respiratory tract irritation.

STOT-repeated exposure

Component 100-41-4:

Repeated exposure affected liver, kidneys

Component 67-64-1:

No data

Component 110-43-0:

No data

Component 123-86-4:

No data

Component 540-88-5:

No data

Routes of Exposure:

Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.

12. Ecological Information

Environmental Toxicity:

Component 100-41-4:

LC50: <10 mg/l (fish); EC50: <10 mg/l (daphnia); EC50: <10 mg/l (algae); EC50:
<10 mg/l (bacteria)

Component 67-64-1:

LC50: 6100 mg/l (fish); EC50: 7630 mg/l (daphnia)

Component 110-43-0:

LC50: 131 mg/l (fish); EC50: >90.1 mg/l (daphnia); EC50: 98.2 mg/l (algae);
EC50: <10 mg/l (bacteria)

Component 123-86-4:

LC50: 100 mg/l (fish); EC50: 72.8-205 mg/l (daphnia)

Component 540-88-5:

Low toxicity: fish, daphnia; EC50: 16 mg/l (algae); EC50: 1.5 mg/l (bacteria)

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 11 of 15

Persistence & degradability:

Component 100-41-4:
Readily biodegradable

Component 67-64-1:
Readily biodegradable

Component 110-43-0:
Readily biodegradable

Component 123-86-4:
No Data

Component 540-88-5:
Inherently biodegradable

Bioaccumulative potential:

Component 100-41-4:
Does not bioaccumulate

Component 67-64-1:
Does not bioaccumulate

Component 110-43-0:
No Data

Component 123-86-4:
No Data

Component 540-88-5:
Not expected to bioaccumulate

Mobility in soil:

Component 100-41-4:
Mobile; may contaminate groundwater

Component 67-64-1:
no data

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 12 of 15

Component 110-43-0:

No data

Component 123-86-4:

No data

Component 540-88-5:

No data

Other Adverse Ecological Effects:

Component 100-41-4:

Dissolved material evaporates rapidly - within a day from water or soil surfaces.

Component 540-88-5:

Harmful to aquatic life.

13. Disposal Considerations

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 13 of 15

material as supplied, it meets RCRA's characteristic definition of ignitability. The toxicity characteristic (TC) has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Federal Regulations may apply to empty container. State and/or local regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2) incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Paint Related Material

UN/NA ID No: UN1263

Hazard Class: Class 3 (IATA/49CFR)

Packing Group: II

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

15. Regulatory Information

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 14 of 15

Canadian Environmental Protection Act (CEPA):
INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

"+" Indicates a Clean Air Act Hazardous Air Pollutant (HAP).

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 05/22/15

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards

which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No

representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any

other nature are made hereunder with respect to the information contained herein or the chemical to which the

information refers. These data relate only to the specific material designated herein and do not relate to use in

combination with any other material. It is the responsibility of the user to comply with all applicable federal, state

and local laws and regulations.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-22750G 26307 GRAY TYPE II CLASS H GR-A - GALLON

Date Printed: 5/22/2015

Page 15 of 15

End of Material Safety Data Sheet