

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 1 of 14

1. Product and Company Identification

Product Name : MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON
Product Code : 852851-36375-GL
Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Randolph Products Company
33 Haynes Circle
Chicopee, MA 01020

Information Phone: 413-592-4191
Emergency Phone: ChemTel 800-255-3924

2. Hazards Identification

EMERGENCY OVERVIEW

DANGER

Highly Flammable Liquid & Vapor, Category 2
Acute Toxicity, Category 4
Skin Irritation, Category 2
Eye Irritation, Category 2B

Chronic Toxicity, Aspiration Hazard, Category 1
Chronic Toxicity, (Carcinogenicity) Category 1



Potential Health Effects

Eye:
Causes eye irritation.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 2 of 14

Skin:

Causes skin irritation.

Ingestion:

If swallowed, call a poison control center or physician if you feel unwell.

Rinse mouth.

Inhalation:

May cause drowsiness or dizziness.

Chronic (Cancer) Information:

Contains CRYSTALLINE SILICA, which can be a health hazard. Respirable crystalline silica can cause the occupational lung disease silicosis (a scarring of the lungs), and IARC concluded in October 1996 that crystalline silica is carcinogenic to humans. Silicosis increases the risk of tuberculosis, autoimmune and chronic kidney diseases, as well as non-malignant respiratory disease (such as chronic bronchitis and emphysema). IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: A component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: A component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

Reproduction Information:

INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:

Dermatitis or other skin conditions.

3. Composition/Information on Ingredients

| Component | CAS# | % by Wt. |
|------------------------------------|------------|----------|
| BARITE | 13462-86-7 | 12 |
| ACGIH: 10 MG/M3 TWA | | |
| OSHA: 15 MG/M3 TWA | | |
| # MICROCRYSTALLINE SILICA (QUARTZ) | 14808-60-7 | 12 |
| ACGIH: 10 MG/M3 TWA, TOTAL DUST | | |
| OSHA: 20 MPPCF3 TWA | | |
| TALC | 14807-96-6 | 12 |

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 3 of 14

| | | |
|-------------------------------------------|-------------|-------|
| ACGIH TLV: 2 MG/M3 TWA, RESPIRABLE DUST | | |
| OSHA PEL: 20 MPPCF TWA | | |
| TITANIUM DIOXIDE | 13463-67-7 | 9.005 |
| ACGIH: 10 MG/M3 TWA | | |
| OSHA: 10 MG/M3 TWA | | |
| METHYL ETHYL KETONE | 78-93-3 | 9 |
| ACGIH: 200 PPM TWA | | |
| OSHA: 200 PPM TWA | | |
| METHYL NORMAL AMYL KETONE | 110-43-0 | 6 |
| OSHA PEL 100 PPM - TWA | | |
| OSHA VEEL 100 PPM -TWA | | |
| ACGIH TLV 50 PPM - TWA | | |
| ACGIH TLV 233 MG/M3 - TWA | | |
| N-BUTYL ACETATE | 123-86-4 | 5 |
| ACGIH: 150 PPM TWA | | |
| OSHA: 150 PPM TWA | | |
| ACGIH: 200 PPM STEL | | |
| OSHA: 200 PPM CEILING | | |
| MODIFIED OXAZOLIDINE | 145899-78-1 | 5 |
| NOT ESTABLISHED | | |
| HYDRATED AMORPHOUS SILICA | 112926-00-8 | 4 |
| ACGIH: 10 MG/M3 TWA, TOTAL DUST | | |
| OSHA: 6 MG/M3 TWA | | |
| *+METHYL ISOBUTYL KETONE | 108-10-1 | 2 |
| ACGIH TLV: 50 PPM TWA | | |
| ACGIH TLV: 75 PPM STEL | | |
| OSHA PEL: 100 PPM TWA | | |
| TERTIARY BUTYL ACETATE | 540-88-5 | 2 |
| ACGIH: 200 PPM TWA | | |
| OSHA: 200 PPM TWA | | |
| PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE | 108-65-6 | 1 |
| SUPPLIER RECOMMENDED: 30 PPM TWA | | |
| 2,4-PENTANEDIONE | 123-54-6 | 1 |
| EXPOSURE LIMITS: NOT ESTABLISHED | | |

4. First Aid Measures

Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 4 of 14

Ingestion:

If swallowed: Immediately call a poison center/physician.

Do NOT induce vomiting.

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison control center/get medical attention if you feel unwell.

Note to Physicians:

INFORMATION NOT AVAILABLE.

5. Fire Fighting Measures

Flammable Properties:

Flash Point: 20 F

Method:

Explosive Limits:

Lower explosive limit: 1.1

Upper explosive limit: 11.4

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 5 of 14

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/state/federal regulations.

7. Handling and Storage

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 6 of 14

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 175 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: n/a

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.457

Coating VOC: 3.03 lb/gl

Material VOC: 2.94 lb/gl

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 7 of 14

INFORMATION NOT AVAILABLE.

Hazardous Polymerization:

Will not occur under normal conditions.

11. Toxicological Information

Eye Irritation/Damage:

Component 110-43-0:

Mild eye irritation, Category 2b

Component 540-88-5:

Based on available data, the classification criteria are not met.

Skin Irritation/Damage:

Component 110-43-0:

LD50: >2000 mg/kg, rat. Category 5

Component 540-88-5:

LD50: >2000 mg/kg, rabbit. Category 5.

Acute Oral Toxicity:

Component 14808-60-7:

LD50: >5000 mg/kg, rat. Category 5

Component 13463-67-7:

LD50: 10,000 mg/kg, rat. Category 5

Component 108-10-1:

LD50: 2080 mg/kg, rat. Category 4

Component 110-43-0:

LD50: 1670 mg/kg, rat. Category 4

Component 123-86-4:

LD50: 10,700 mg/kg, rat. Category 5

Component 540-88-5:

LD50: 4,500 mg/kg, rat. Category 5

Component 108-65-6:

LD50: no data

Acute Inhalation Toxicity:

Component 110-43-0:

LD50: >16.7 mg/kg, rat. Category 4

Component 540-88-5:

LC50: 12.52 mg/l, rat. Category 2

Respiratory/Skin Sensitization:

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 8 of 14

Component 110-43-0:
No evidence of respiratory or skin sensitization.

Component 540-88-5:
No evidence of respiratory or skin sensitization.

Carcinogenicity:
Component 13463-67-7:
Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans). GHS Category 2.

Component 14808-60-7:
Listed by IARC as a group 1 carcinogen (carcinogenic to humans), and as a known carcinogen by NTP. GHS Category 1A.

Component 110-43-0:
Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Component 540-88-5:
Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Reproductive Toxicity:
Component 110-43-0:
No evidence of human reproductive toxicity.

Component 540-88-5:
No evidence of human reproductive toxicity.

Germ Cell Mutagenicity:
Component 110-43-0:
No data

Component 540-88-5:
No data

Aspiration Toxicity:
Component 108-10-1:
Aspiration Hazard; Category 1
Component 110-43-0:
Not classified as an Aspiration Hazard.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 9 of 14

Component 123-86-4:
Not classified as an Aspiration Hazard.

Component 540-88-5:
Not classified as an Aspiration Hazard.

Component 108-65-6:
Not classified as an Aspiration Hazard.

STOT-single exposure
Component 108-10-1:
No data Component 110-43-0:
No data

Component 123-86-4:
No data Component 540-88-5:
Transient target organ effects (Category 3);
Respiratory tract irritation.

Component 108-65-6:
No data

STOT-repeated exposure
Component 108-10-1:
No data Component 110-43-0:
No data

Component 123-86-4:
No data
Component 540-88-5:
No data
Component 108-65-6:
No data

Routes of Exposure:
Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.

12. Ecological Information

Environmental Toxicity:
Component 108-10-1:
LC50: 505 mg/l (fish); EC50: 1000 mg/l (daphnia); EC50: 980 mg/l (algae)
Component 110-43-0:
LC50: 131 mg/l (fish); EC50: >90.1 mg/l (daphnia); EC50: 98.2 mg/l (algae);
EC50: <10 mg/l (bacteria)

Component 123-86-4:

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 10 of 14

LC50: 100 mg/l (fish); EC50: 72.8-205 mg/l (daphnia)

Component 540-88-5:

Low toxicity: fish, daphnia; EC50: 16 mg/l (algae); EC50: 1.5 mg/l (bacteria)

Component 108-65-6:

LC50: 161 mg/l (fish); EC50: 373 mg/l (daphnia); EC50: >1000 mg/l (algae)

Persistence & degradability:

Component 108-10-1:

Readily biodegradable

Component 110-43-0:

Readily biodegradable

Component 123-86-4:

No Data

Component 540-88-5:

Inherently biodegradable

Component 108-65-6:

Readily biodegradable

Bioaccumulative potential:

Component 108-10-1:

No Data

Component 110-43-0:

No Data

Component 123-86-4:

No Data

Component 540-88-5:

Not expected to bioaccumulate

Component 108-65-6:

No Data

Mobility in soil:

Component 108-10-1:

No data

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 11 of 14

Component 110-43-0:

No data

Component 123-86-4:

No data

Component 540-88-5:

No data

Component 108-65-6:

No data

Other Adverse Ecological Effects:

Component 540-88-5:

Harmful to aquatic life.

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 12 of 14

13. Disposal Considerations

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this material as supplied, it meets RCRA's characteristic definition of ignitability. The toxicity characteristic (TC) has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Federal Regulations may apply to empty container. State and/or local regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2) incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Paint

UN/NA ID No: UN1263

Hazard Class: Class 3 (IATA/49CFR)

Packing Group: II

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

15. Regulatory Information

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std. Not regarded as a health hazard under current

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 13 of 14

legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

"+" Indicates a Clean Air Act Hazardous Air Pollutant (HAP).

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 06/10/15

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards

SAFETY DATA SHEET

Randolph Products Company

MIL-PRF-85285E 36375 TYPE 1 AND 2 CLASS H - GALLON

Date Printed: 6/10/2015

Page 14 of 14

which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. These data relate only to the specific material designated herein and do not relate to use in combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet