

# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 1 of 14

---

### **1. Product and Company Identification**

---

Product Name : MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Product Code : 852851-37038-GL

Recommended Use: Please refer to Product Information/Technical Data Sheet.

#### Company Identification:

Randolph Products Company  
33 Haynes Circle  
Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

### **2. Hazards Identification**

---

#### EMERGENCY OVERVIEW

#### DANGER

Highly Flammable Liquid & Vapor, Category 2

Acute Toxicity, Category 4

Skin Irritation, Category 2

Eye Irritation, Category 2B

Aspiration Hazard, Category 1

Chronic Toxicity, (Carcinogenicity) Category 1



#### Potential Health Effects

##### Eye:

Causes eye irritation.

# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 2 of 14

---

### Skin:

Causes skin irritation.

### Ingestion:

If swallowed, call a poison control center or physician if you feel unwell.

Rinse mouth.

### Inhalation:

May cause drowsiness or dizziness.

### Chronic (Cancer) Information:

Contains CRYSTALLINE SILICA, which can be a health hazard. Respirable crystalline silica can cause the occupational lung disease silicosis (a scarring of the lungs), and IARC concluded in October 1996 that crystalline silica is carcinogenic to humans. Silicosis increases the risk of tuberculosis, autoimmune and chronic kidney diseases, as well as non-malignant respiratory disease (such as chronic bronchitis and emphysema). Contains CARBON BLACK, which is listed by the IARC as a Group 2B (possibly carcinogenic to humans). Not listed as a carcinogen by NTP, ACGIH, OSHA or the European Union. There are no known human carcinogenic effects related to the PAH content in carbon blacks. Recent research has shown that the PAH content of carbon blacks is not released in biological fluids and thus not available for biological activity.

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: A component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: A component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

### Reproduction Information:

INFORMATION NOT AVAILABLE.

### Aggravation of Pre-Existing Conditions:

Dermatitis or other skin conditions.

## **3. Composition/Information on Ingredients**

---

Component

CAS#

% by Wt.

# SAFETY DATA SHEET

## *Randolph Products Company*

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 3 of 14

---

# MICROCRYSTALLINE SILICA (QUARTZ)	14808-60-7	15
ACGIH: 10 MG/M3 TWA, TOTAL DUST		
OSHA: 20 MPPCF3 TWA		
BARITE	13462-86-7	13
ACGIH: 10 MG/M3 TWA		
OSHA: 15 MG/M3 TWA		
TALC	14807-96-6	11
ACGIH TLV: 2 MG/M3 TWA, RESPIRABLE DUST		
OSHA PEL: 20 MPPCF TWA		
METHYL ETHYL KETONE	78-93-3	9
ACGIH: 200 PPM TWA		
OSHA: 200 PPM TWA		
METHYL NORMAL AMYL KETONE	110-43-0	6
OSHA PEL 100 PPM - TWA		
OSHA VPEL 100 PPM -TWA		
ACGIH TLV 50 PPM - TWA		
ACGIH TLV 233 MG/M3 - TWA		
N-BUTYL ACETATE	123-86-4	5
ACGIH: 150 PPM TWA		
OSHA: 150 PPM TWA		
ACGIH: 200 PPM STEL		
OSHA: 200 PPM CEILING		
MODIFIED OXAZOLIDINE	145899-78-1	4
NOT ESTABLISHED		
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	108-65-6	4
SUPPLIER RECOMMENDED: 30 PPM TWA		
HYDRATED AMORPHOUS SILICA	112926-00-8	3
ACGIH: 10 MG/M3 TWA, TOTAL DUST		
OSHA: 6 MG/M3 TWA		
*+# METHYL ISOBUTYL KETONE	108-10-1	2
ACGIH TLV: 50 PPM TWA		
ACGIH TLV: 75 PPM STEL		
OSHA PEL: 100 PPM TWA		
# CARBON BLACK	1333-86-4	1.216
ACGIH: 3.5 MG/M3 TWA		
OSHA: 3.5 MG/M3 TWA		
2,4-PENTANEDIONE	123-54-6	1
EXPOSURE LIMITS: NOT ESTABLISHED		
TERTIARY BUTYL ACETATE	540-88-5	1
ACGIH: 200 PPM TWA		
OSHA: 200 PPM TWA		

#### **4. First Aid Measures**

---

##### Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 4 of 14

---

If eye irritation persists: Get medical advice/attention.

### Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs:  
Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

### Ingestion:

If swallowed: Immediately call a poison center/physician.  
Do NOT induce vomiting.

### Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Call a poison control center/get medical attention if you feel unwell.

### Note to Physicians:

INFORMATION NOT AVAILABLE.

## **5. Fire Fighting Measures**

---

### Flammable Properties:

Flash Point: 20 F Method:

### Explosive Limits:

Lower explosive limit: 1.1  
Upper explosive limit: 11.4

### Autoignition Temperature:

INFORMATION NOT AVAILABLE.

### Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

### Extinguishing Media:

Dry chemical, CO2, Halon, Foam

### Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

## **6. Accidental Release Measures**

---

# SAFETY DATA SHEET

## ***Randolph Products Company***

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 5 of 14

---

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/state/federal regulations.

## **7. Handling and Storage**

---

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

## **8. Exposure Controls/Personal Protection**

---

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special

circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 6 of 14

---

### Personal Protective Equipment

#### Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

#### Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

#### Eye Protection:

Chemical safety goggles or glasses with side shields.

### **9. Physical and Chemical Properties**

---

Boiling Point: 175 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: n/a

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.37

Coating VOC: 3.21 lb/gl

Material VOC: 3.16 lb/gl

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

# SAFETY DATA SHEET

## ***Randolph Products Company***

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 7 of 14

---

### **10. Stability and Reactivity**

---

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

INFORMATION NOT AVAILABLE.

Hazardous Polymerization:

Will not occur under normal conditions.

---

### **11. Toxicological Information**

---

Eye Irritation/Damage:

Component 110-43-0:

Mild eye irritation, Category 2b

Component 540-88-5:

Based on available data, the classification criteria are not met.

Skin Irritation/Damage:

Component 110-43-0:

LD50: >2000 mg/kg, rat. Category 5

Component 540-88-5:

LD50: >2000 mg/kg, rabbit. Category 5.

Acute Oral Toxicity:

Component 1333-86-4:

LD50: >8000 mg/kg, rat. Category 5

Component 14808-60-7:

LD50: >5000 mg/kg, rat. Category 5

Component 108-10-1:

LD50: 2080 mg/kg, rat. Category 4

Component 110-43-0:

LD50: 1670 mg/kg, rat. Category 4

Component 123-86-4:

LD50: 10,700 mg/kg, rat. Category 5

Component 540-88-5:

LD50: 4,500 mg/kg, rat. Category 5

Component 108-65-6:

LD50: no data

Acute Inhalation Toxicity:

# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 8 of 14

---

Component 110-43-0:

LD50: >16.7 mg/kg, rat. Category 4

Component 540-88-5:

LC50: 12.52 mg/l, rat. Category 2

Respiratory/Skin Sensitization:

Component 110-43-0:

No evidence of respiratory or skin sensitization.

Component 540-88-5:

No evidence of respiratory or skin sensitization.

Carcinogenicity:

Component 1333-86-4:

Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans).

Carbon Black is not listed as a carcinogen by

NTP, OSHA or ACGIH. GHS Category 2.

Component 14808-60-7:

Listed by IARC as a group 1 carcinogen (carcinogenic to humans), and as a known carcinogen by NTP. GHS Category 1A.

Component 110-43-0:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Component 540-88-5:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH.

Reproductive Toxicity:

Component 110-43-0:

No evidence of human reproductive toxicity.

Component 540-88-5:

No evidence of human reproductive toxicity.

Germ Cell Mutagenicity:

Component 110-43-0:

No data

Component 540-88-5:

No data



# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 9 of 14

---

### Aspiration Toxicity:

Component 108-10-1:

Aspiration Hazard; Category 1

Component 110-43-0:

Not classified as an Aspiration Hazard.

Component 123-86-4:

Not classified as an Aspiration Hazard.

Component 540-88-5:

Not classified as an Aspiration Hazard.

Component 108-65-6:

Not classified as an Aspiration Hazard.

### STOT-single exposure

Component 108-10-1:

No data Component 110-43-0:

No data

Component 123-86-4:

No data Component 540-88-5:

Transient target organ effects (Category 3);

Respiratory tract irritation.

Component 108-65-6:

No data

### STOT-repeated exposure

Component 108-10-1:

No data Component 110-43-0:

No data

Component 123-86-4:

No data

Component 540-88-5:

No data

Component 108-65-6:

No data

### Routes of Exposure:

Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.

## **12. Ecological Information**

---

### Environmental Toxicity:

Component 1333-86-4:

# SAFETY DATA SHEET

## *Randolph Products Company*

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 10 of 14

---

LC50: <1000 mg/l (fish); EC50: <5600 mg/l (daphnia); EC50: <10,000 mg/l (algae)

Component 108-10-1:

LC50: 505 mg/l (fish); EC50: 1000 mg/l (daphnia); EC50: 980 mg/l (algae)

Component 110-43-0:

LC50: 131 mg/l (fish); EC50: >90.1 mg/l (daphnia); EC50: 98.2 mg/l (algae);

EC50: <10 mg/l (bacteria)

Component 123-86-4:

LC50: 100 mg/l (fish); EC50: 72.8-205 mg/l (daphnia)

Component 540-88-5:

Low toxicity: fish, daphnia; EC50: 16 mg/l (algae); EC50: 1.5 mg/l (bacteria)

Component 108-65-6:

LC50: 161 mg/l (fish); EC50: 373 mg/l (daphnia); EC50: >1000 mg/l (algae)

Persistence & degradability:

Component 1333-86-4:

Carbon Black is essentially elemental carbon & cannot be further biodegraded by microorganisms.

Component 108-10-1:

Readily biodegradable

Component 110-43-0:

Readily biodegradable

Component 123-86-4:

No Data

Component 540-88-5:

Inherently biodegradable

Component 108-65-6:

Readily biodegradable

Bioaccumulative potential:

Component 1333-86-4:

Not expected to bioaccumulate.

Component 108-10-1:

No Data

Component 110-43-0:

No Data

Component 123-86-4:

No Data

Component 540-88-5:

Not expected to bioaccumulate

# SAFETY DATA SHEET

## *Randolph Products Company*

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 11 of 14

---

Component 108-65-6:

No Data

Mobility in soil:

Component 108-10-1:

No data

Component 110-43-0:

No data

Component 123-86-4:

No data

Component 540-88-5:

No data

Component 108-65-6:

No data

# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 12 of 14

---

Other Adverse Ecological Effects:

Component 540-88-5:

Harmful to aquatic life.

### **13. Disposal Considerations**

---

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this material as supplied, it meets RCRA's characteristic definition of ignitability. The toxicity characteristic (TC) has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Federal Regulations may apply to empty container. State and/or local regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2) incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

### **14. Transport Information**

---

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Paint

UN/NA ID No: UN1263

Hazard Class: Class 3 (IATA/49CFR)

Packing Group: II

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

# SAFETY DATA SHEET

## **Randolph Products Company**

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 13 of 14

Special Precautions for User:  
INFORMATION NOT AVAILABLE.

### **15. Regulatory Information**

---

U.S. Federal Regulations:

TSCA: All components of this material are on the  
US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

This product is hazardous under OSHA's Hazard Communication Std. Not regarded  
as a health hazard under current  
legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"\*" Indicates toxic chemical(s) subject to the reporting requirements of  
section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth  
defects or other reproductive harm.

"+" Indicates a Clean Air Act Hazardous Air Pollutant (HAP).

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of  
coating less water and exempt solvents, where  
applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

### **16. Other Information**

---

Date Revised: 06/03/15

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all  
possible individual situations. As the  
user has the responsibility to provide a safe workplace, all aspects of an  
individual operation should be examined to

# SAFETY DATA SHEET

## *Randolph Products Company*

MIL-PRF-85285E 37038 TYPE 1 AND 2 CL-H - GALLON

Date Printed: 6/3/2015

Page 14 of 14

---

determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. These data relate only to the specific material designated herein and do not relate to use in combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet