

**Randolph Products Company**

33 Haynes Circle

Chicopee, MA 01020

Telephone 413-592-4191

Facsimile: 413-594-7321

**8D44 BC LINEN ALKYD PRIMER**

GENERAL INFORMATION	PHYSICAL PROPERTIES	APPLICATION
<p>A high performance alkyd primer designed for use over raw lumber.</p> <p>This product has a fast dry time, excellent weatherability, good mold and mildew resistance, good flexibility and good stain blocking properties.</p> <p>Randolph Products Co. warrants that its products meet its internal specifications and are of merchantable quality. However, the purchaser is solely responsible for the suitability of the product for any particular application. The purchaser should thoroughly test or qualify the product for serviceability, environmental compliance and health and safety factors prior to use. Further, our total liability is limited to the price of the product or replacement in kind.</p> <p>Randolph Products Company 33 Haynes Circle Chicopee, MA 01020 Phone: 413-592-4191 Fax: 413-594-7321 www.randolphproducts.com</p>	<ol style="list-style-type: none"> <li>1. <b>Color:</b> BC Linen</li> <li>2. <b>Volume Solids:</b> 58 +/- 2%</li> <li>3. <b>Solids by Weight:</b> 78 +/- 2%</li> <li>4. <b>Viscosity:</b> 19 seconds max. #3 Zahn</li> <li>5. <b>DFT:</b> 2 – 4 mils dft</li> <li>6. <b>Theoretical Coverage @ 1 mil dft:</b> 930 ft<sup>2</sup>/gallon</li> <li>7. <b>Gloss @ 60°</b> 3 maximum</li> <li>8. <b>Dry Time</b> Set to Touch: 2 hours max. To Recoat: Overnight</li> <li>9. <b>VOC</b> 2.8 lbs/gallon (340 grams/liter)- maximum</li> </ol>	<p><b>Application Methods:</b> Use conventional spray, airless spray or flowcoat.</p> <p>Surface must be clean and free of grease, dirt, oil, and other contaminants that could interfere with proper adhesion.</p> <p><b>Reduction:</b> Reduce with Mineral Spirits as needed.</p> <p><b>Clean-up:</b> Clean tools and equipment immediately after use with Mineral Spirits.</p> <p><b>Safety Precautions:</b> This product is intended for professional use in an industrial environment only. Consult the Material Safety Data Sheet prior to application.</p>