Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 1 of 12

1. Product and Company Identification

Product Name : TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Product Code : 28H-GL

Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Randolph Products Company

33 Haynes Circle Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

2. Hazards Identification

EMERGENCY OVERVIEW

DANGER

Flammable Liquid & Vapor, Category 3 Acute Toxicity, Category 4 Skin Irritation, Category 2 Eye Irritation, Category 2B

Chronic Toxicity, Aspiration Hazard, Category 1







Potential Health Effects

Eye:

Causes eye irritation.

Skin:

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 2 of 12

Causes skin irritation.

Ingestion:

If swallowed, call a poison control center or physician if you feel unwell. Rinse mouth.

Inhalation:

May cause drowsiness or dizziness.

Chronic (Cancer) Information:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probably, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at leveles greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at leveles greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No component of this product present at leveles greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

No specific information.

Reproduction Information:

No specific information.

Aggravation of Pre-Existing Conditions:

Dermititis or other skin conditions.

3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
PARA-CHLOROBENZOTRIFLUORIDE	98-56-6	47
(SUPPLIER): 20 PPM TWA * ALUMINUM * ACCID: 10 MC/M2 TWA	7429-90-5	22
ACGIH: 10 MG/M3 TWA OSHA: 15 MG/M3 TWA		
WHITE SPIRITS ACGIH TLV: NONE ESTABLISHED	64742-82-1	8
OSHA PEL: NONE ESTABLISHED SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC OSHA PEL: 500 PPM (2000 MG/M3)	64742-95-6	2
ACGIH TLV: 200 MG/M3 (AS TOTAL HYDROCARBON VAPOR)		

4. First Aid Measures

Eyes:

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 3 of 12

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Ingestion:

If swallowed: Immediately call a poison center/physician.

Do NOT induce vomiting.

Inhalation:

If symptomatic, move to fresh air. Get medical attention if symptoms persist.

Note to Physicians:

Aspiration hazard - do not induce vomiting

5. Fire Fighting Measures

Flammable Properties:

Flash Point: 100 F Method: SCC

Explosive Limits:

Lower explosive limit: 0.9 Upper explosive limit: 10.5

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of

internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 4 of 12

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to

safe areas. Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

Environmental Precautions:

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material,

(e.g. sand earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local/state/federal regulations.

7. Handling and Storage

Handling:

Avoid storage in high humidity areas or where moisture contamination could occur. Keep away from heat, sparks, open

flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

INFORMATION NOT AVAILABLE.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special

circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 5 of 12

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 282 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: -63F

Vapor Pressure:

INFORMATION NOT AVAILABLE.

Vapor Density: HEAVIER THAN AIR Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.371

Weight per Gallon: 11.415 lb/gl

Coating VOC: 250 G/LITER

Material VOC: 250 G/LITER

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 6 of 12

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):
Stable under normal storage/use conditions.
Incompatibility:
Avoid strong oxidizing agents, acids and alkalies.
Hazardous Decomposition Products:
INFORMATION NOT AVAILABLE.
Hazardous Polymerization:
Will not occur under normal conditions.

```
11. Toxicological Information
Eye Irritation/Damage:
Component 64742-95-6:
Mild eye irritation, Category 2b
Component 98-56-6:
Mild eye irritation, Category 2b.
Skin Irritation/Damage:
Component 64742-95-6:
LD50: >2000 mg/kg, rat. Category 5
Component 98-56-6:
LD50: No data
Mild skin irritation.
Acute Oral Toxicity:
Component 64742-95-6:
LD50: >5000 mg/kg, rat. Category 5
Component 98-56-6:
LD50: 13000 mg/kg, rat. Category 5
Acute Inhalation Toxicity:
Component 64742-95-6:
LC50: 5.6 mg/l, rat. Category 3
Component 98-56-6:
LC50: 33 mg/l, rat. Category 5
```

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 7 of 12

Respiratory/Skin Sensitization: Component 64742-95-6: No evidence of respiratory or skin sensitization. Component 98-56-6: No evidence of respiratory or skin sensitization. Carcinogenicity: Component 64742-95-6: Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH Component 98-56-6: Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH Reproductive Toxicity: Component 64742-95-6: No evidence of human reproductive toxicity. Component 98-56-6: No evidence of human reproductive toxicity. Germ Cell Mutagenicity: Component 64742-95-6: No data Component 98-56-6: No data

Aspiration Toxicity: Component 64742-95-6: Aspiration Hazard; Category 1

Randolph Products Company

```
TT-P-28H HEAT RESISTING ALUMINUM - GALLON
Date Printed: 9/23/2015
Page 8 of 12
Component 98-56-6:
Not classified as an Aspiration Hazard.
STOT-single exposure
Component 64742-95-6:
No data
Component 98-56-6:
No data
STOT-repeated exposure
Component 64742-95-6:
Repeated exposure affected kidneys, blood, adrenal gland.
Component 98-56-6:
No data
Routes of Exposure:
Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.
12. Ecological Information
Environmental Toxicity:
Component 64742-95-6:
LC50: 10 mg/l (fish); EC50: 4.5 mg/l (daphnia); EC50: 3.1 mg/l (algae)
Component 98-56-6:
LC50: 5.6 mg/l (fish)
Persistance & degradability:
Component 64742-95-6:
Readily biodegradable
```

Component 98-56-6: Readily biodegradable

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 9 of 12

Bioaccumulative potential: Component 64742-95-6: No Data Component 98-56-6: No data.

Mobility in soil: Component 64742-95-6: No data Component 98-56-6: no data

Other Adverse Ecological Effects: No information

Component 64742-95-6: Toxic to aquatic life with long lasting results.

13. Disposal Considerations

Waste Disposal Method: Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 10 of 12

material as supplied, it meets RCRA's characteristic definition of ignitability. The toxicity characteristic (TC) has

not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

Federal Regulations may apply to empty container. State and/or local

regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the

following order of preference, based upon environmental acceptability: (1)

recycle or rework, if feasible; (2)

incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO)

Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Not regulated by DOT, COMBUSTIBLE LIQUID*

UN/NA ID No: n/a Hazard Class: n/a Packing Group: n/a

*NOT REGULATED BY GROUND TRANSPORTATION IN NON-BULK PACKAGING (450L OR 119

GALLONS OR LESS) PER CFR 173.150 (f) (2).

IF SHIPPED BY AIR, VESSEL OR IN BULK THEN:

Shipping name: Paint UN/NA ID No: UN1263 Hazard Class: 3 Packing Group: III

Environmental Hazards:

INFORMATION NOT AVAILABLE.

Marine Pollutant:

Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:

INFORMATION NOT AVAILABLE.

15. Regulatory Information

U.S. Federal Regulations:

TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 11 of 12

This product is hazardous under OSHA's Hazard Communication Std. Not regarded as a health hazard under current

legislation.

CERCLA: SARA Hazard Category:

INFORMATION NOT AVAILABLE.

Section 313:

"*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:

INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):

INFORMATION NOT AVAILABLE.

EINECS:

INFORMATION NOT AVAILABLE.

State Regulations:

INFORMATION NOT AVAILABLE.

Volatile Organic Compounds:

COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where applicable.

MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 09/23/15

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the

user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to

determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and

safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no

liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be

used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards

which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No

Randolph Products Company

TT-P-28H HEAT RESISTING ALUMINUM - GALLON

Date Printed: 9/23/2015

Page 12 of 12

representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any

other nature are made hereunder with respect to the information contained herein or the chemical to which the

information refers. These data relate only to the specific material designated herein and do not relate to use in

combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet