

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOG RIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 1 of 15

1. Product and Company Identification

Product Name : RANDOG RIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4

Product Code : 600D02-PL

Recommended Use: Please refer to Product Information/Technical Data Sheet.

Company Identification:

Eastern Chem-Lac
33 Haynes Circle
Chicopee, MA 01020

Information Phone: 413-592-4191

Emergency Phone: ChemTel 800-255-3924

2. Hazards Identification

EMERGENCY OVERVIEW

HAZARD CLASSIFICATION:

FLAMMABLE LIQUID, CATEGORY 3

ACUTE TOXICITY (ORAL), CATEGORY 3

SKIN IRRITATION, CATEGORY 2

EYE IRRITATION, CATEGORY 2B

ASPIRATION HAZARD, CATEGORY 1

CARCINOGENICITY, CATEGORY 2

SIGNAL WORD:

DANGER



HAZARD STATEMENTS:

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 2 of 15

FLAMMABLE LIQUID AND VAPOR
HARMFUL IF SWALLOWED
CAUSES SKIN IRRITATION
CAUSES EYE IRRITATION
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS
SUSPECTED OF CAUSING CANCER

PRECAUTIONARY STATEMENTS:

Keep away from heat, sparks, open flame/hot surfaces.
No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting and other equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Store/Use outdoors or in a well ventilated place.
Keep cool.
Store locked up.
Wash hands thoroughly after handling.
Do not eat or drink while using this product.
Do not breathe vapors.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If swallowed, immediately call a poison control center.
Rinse mouth.
Wear protective gloves, protective clothing, eye/face protection.
If on skin or hair: Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation occurs, seek medical advice.
Take off contaminated clothing and wash it before reuse.
If exposed or concerned, get medical advice or attention.
Call a poison center or doctor if you feel unwell.
If in eyes, rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: get medical attention.
In case of fire: Use dry chemical, CO₂, Halon or foam to extinguish.
Dispose of contents/container in accordance with all local, regional, national regulations.
Do NOT induce vomiting.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.

Potential Health Effects

Eye:
Can cause eye irritation.
Skin:
Causes skin irritation.
Ingestion:
If swallowed, call a poison control center or physician if you feel unwell.
Rinse mouth.

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 3 of 15

Inhalation:

May cause drowsiness or dizziness.

Chronic (Cancer) Information:

Contains CARBON BLACK, which is listed by the IARC as a Group 2B (possibly carcinogenic to humans). Not listed as a carcinogen by NTP, ACGIH, OSHA or the European Union. There are no known human carcinogenic effects related to the PAH content in carbon blacks. Recent research has shown that the PAH content of carbon blacks is not released in biological fluids and thus not available for biological activity.

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Teratology (Birth Defects) Information:

INFORMATION NOT AVAILABLE.

Reproduction Information:

INFORMATION NOT AVAILABLE.

Aggravation of Pre-Existing Conditions:

Dermatitis or other skin conditions.

3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
NEPHELINE SYENITE	37244-96-5	34
OSHA: 5MG/M3 TWA (RESPIRABLE FRACTION)		
ACGIH: 10 MG/M3 TWA (INHALABLE FRACTION)		
MSHA 5 MG/M3 TWA (RESPIRABLE FRACTION)		
TALC	14807-96-6	10
OSHA: 2 MG/M3		
ACGIH: 2 MG/M3		
MAGNESITE	546-93-0	7
OSHA: 5 MG/M3 (RESP DUST)		
ACGIH: 10 MG/M3 (RESP DUST)		
METHYL NORMAL AMYL KETONE	110-43-0	6
OSHA PEL 100 PPM - TWA		
OSHA VPEL 100 PPM -TWA		

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOG RIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 4 of 15

ACGIH TLV 50 PPM - TWA		
ACGIH TLV 233 MG/M3 - TWA		
# TITANIUM DIOXIDE	13463-67-7	5.415
ACGIH: 10 MG/M3 TWA		
OSHA: 10 MG/M3 TWA		
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC	64742-95-6	5
OSHA PEL: 500 PPM (2000 MG/M3)		
ACGIH TLV: 200 MG/M3 (AS TOTAL HYDROCARBON VAPOR)		
1-METHOXY 2-PROPANOL	107-98-2	4
ACGIH: 100 PPM TWA		
OSHA: 100 PPM TWA		
ACGIH: 150 PPM STEL		
OSHA: 150 PPM CEILING		
EPOXY RESIN	25036-25-3	4
* ZINC PHOSPHATE	7779-90-0	3
NONE ESTABLISHED; SARA 313 REPORTABLE AS "ZINC COMPOUNDS"		
N-BUTYL ACETATE	123-86-4	1
ACGIH: 150 PPM TWA		
OSHA: 150 PPM TWA		
ACGIH: 200 PPM STEL		
OSHA: 200 PPM CEILING		
# CARBON BLACK, AMORPHOUS	1333-86-4	.541
ACGIH TLV: 3.5 MG/M3 TWA		
OSHA PEL: 3.5 MG/M3 TWA		
# ETHYL BENZENE	100-41-4	.079
ACGIH TLV 100 PPM - TWA		
OSHA PEL 100 PPM - TWA		
OSHA PEL 100 PPM - TWA		
OSHA PEL 125 PPM - CEILING		

4. First Aid Measures

Eyes:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin:

If on skin: wash with plenty of soap & water. If skin irritation occurs: Get Medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Ingestion:

If swallowed: Immediately call a poison center/physician.
Do NOT induce vomiting.

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 5 of 15

Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison control center/get medical attention if you feel unwell.

Note to Physicians:

Aspiration hazard - do not induce vomiting

5. Fire Fighting Measures

Flammable Properties:

Flash Point: 100 F Method: TCC

Explosive Limits:

Lower explosive limit: 1.0
Upper explosive limit: 13.8

Autoignition Temperature:

INFORMATION NOT AVAILABLE.

Hazardous Combustion Products:

Smoke, soot and carbon dioxide, carbon monoxide.

Extinguishing Media:

Dry chemical, CO2, Halon, Foam

Firefighting Procedures:

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards: High temperatures can cause sealed containers to rupture due to a build up of internal pressure. Cool with water spray. Vapors are heavier than air and can travel some distance away and flash back.

Sensitivity to Static Discharge: Material may accumulate a static charge which could act as an ignition source.

Precautions should be taken when pouring to minimize splash/free fall.

6. Accidental Release Measures

Small Spill:

See Information for Large Spill, below:

Large Spill:

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental Precautions:

INFORMATION NOT AVAILABLE.

Methods/Materials for Containment and Cleaning Up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand earth, diatomaceous earth,

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 6 of 15

vermiculite) and place in container for disposal according to local/state/federal regulations.

7. Handling and Storage

Handling:

Keep away from heat, sparks, open flames, hot surfaces. NO SMOKING. Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/processing equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Storage:

Prevent unauthorized access.

Store in a well ventilated place.

Keep container tightly closed.

Keep cool.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

SEE SECTION 3 FOR THIS INFORMATION

Engineering Controls:

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions.

Ventilation should be explosion proof.

Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special

circumstances such as poorly ventilated spaces, spray painting, mechanical generation of dusts, heating, drying, etc.

Personal Protective Equipment

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be

worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance

with OSHA Standard 63 CFR 1152, January 8, 1998. Respirator type: Organic Vapor.

Skin Protection:

Wear impervious gloves to prevent skin contact.

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 7 of 15

Recommended Decontamination Facilities: eye bath, washing facilities, safety shower.

Eye Protection:

Chemical safety goggles or glasses with side shields.

9. Physical and Chemical Properties

Boiling Point: 248 F

Melting Point:

INFORMATION NOT AVAILABLE.

Freezing Point: -63F

Vapor Pressure:

Information not available for mixture

Vapor Density:

HEAVIER THAN AIR

Solubility in Water:

NEGLIGIBLE

Evaporation Rate: SLOWER THAN ETHER

Specific Gravity: 1.597

Weight per Gallon: 13.296 lb/gal

Coating VOC: 2.26 lb/gal

Material VOC: 2.26 lb/gal

Odor:

Mild solvent odor.

Appearance:

Liquid.

Partition Coefficient:

INFORMATION NOT AVAILABLE.

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal storage/use conditions.

Incompatibility:

Avoid strong oxidizing agents, acids and alkalies.

Hazardous Decomposition Products:

INFORMATION NOT AVAILABLE.

Hazardous Polymerization:

Will not occur under normal conditions.

11. Toxicological Information

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 8 of 15

Eye Irritation/Damage:

Component 100-41-4:

Mild eye irritation, Category 2b

Component 37244-96-5:

Mechanical eye irritation only

Component 64742-95-6:

Mild eye irritation, Category 2b

Skin Irritation/Damage:

Component 100-41-4:

LD50: >2000 mg/kg, rat. Category 5

Component 37244-96-5:

LD50: No data

Component 64742-95-6:

LD50: >2000 mg/kg, rat. Category 5

Acute Oral Toxicity:

Component 100-41-4:

LD50: >2000 mg/kg, rat. Category 5.

Component 1333-86-4:

LD50: >8000 mg/kg, rat. Category 5

Component 37244-96-5:

LD50: no data

Component 13463-67-7:

LD50: 10,000 mg/kg, rat. Category 5

Component 64742-95-6:

LD50: >5000 mg/kg, rat. Category 5

Component 123-86-4:

LD50: 10,700 mg/kg, rat. Category 5

Component 107-98-2:

LD50: 7200 mg/kg, rat. Category 5

Acute Inhalation Toxicity:

Component 100-41-4:

LC50: 2-20 mg/l, rat. Category 3

Component 64742-95-6:

LC50: 5.6 mg/l, rat. Category 3

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 9 of 15

Respiratory/Skin Sensitization:

Component 100-41-4:

No evidence of respiratory or skin sensitization.

Component 37244-96-5:

No evidence of respiratory or skin sensitization.

Component 64742-95-6:

No evidence of respiratory or skin sensitization.

Carcinogenicity:

Component 100-41-4:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 1333-86-4:

Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans).

Carbon Black is not listed as a carcinogen by

NTP, OSHA or ACGIH. GHS Category 2.

Component 13463-67-7:

Listed by IARC as a group 2B carcinogen (possibly carcinogenic to humans). GHS Category 2.

Component 37244-96-5:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Component 64742-95-6:

Not listed as a carcinogen by IARC, NTP, OSHA or ACGIH

Reproductive Toxicity:

Component 100-41-4:

No evidence of human reproductive toxicity.

Component 37244-96-5:

No evidence of human reproductive toxicity.

Component 64742-95-6:

No evidence of human reproductive toxicity.

Germ Cell Mutagenicity:

Component 100-41-4:

No data

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 10 of 15

Component 37244-96-5:

No data

Component 64742-95-6:

No data

Aspiration Toxicity:

Component 100-41-4:

Not classified as an Aspiration Hazard.

Component 37244-96-5:

Not classified as an Aspiration Hazard.

Component 64742-95-6:

Aspiration Hazard; Category 1

Component 123-86-4:

Not classified as an Aspiration Hazard.

Component 107-98-2:

Not classified as an Aspiration Hazard.

STOT-single exposure

Component 100-41-4:

No data

Component 37244-96-5:

No data

Component 64742-95-6:

No data

Component 123-86-4:

No data Component 107-98-2:

No data

STOT-repeated exposure

Component 100-41-4:

Repeated exposure affected liver, kidneys

Component 37244-96-5:

No data

Component 64742-95-6:

Repeated exposure affected kidneys, blood, adrenal gland.

Component 123-86-4:

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 11 of 15

No data

Component 107-98-2:

No data

Routes of Exposure:

Inhalation of vapors, skin/eye/mucous membrane absorption, ingestion.

12. Ecological Information

Environmental Toxicity:

Component 100-41-4:

LC50: <10 mg/l (fish); EC50: <10 mg/l (daphnia); EC50: <10 mg/l (algae); EC50: <10 mg/l (bacteria)

Component 1333-86-4:

LC50: <1000 mg/l (fish); EC50: <5600 mg/l (daphnia); EC50: <10,000 mg/l (algae)

Component 37244-96-5:

No data

Component 64742-95-6:

LC50: 10 mg/l (fish); EC50: 4.5 mg/l (daphnia); EC50: 3.1 mg/l (algae)

Component 123-86-4:

LC50: 100 mg/l (fish); EC50: 72.8-205 mg/l (daphnia)

Persistence & degradability:

Component 100-41-4:

Readily biodegradable

Component 1333-86-4:

Carbon Black is essentially elemental carbon & cannot be further biodegraded by microorganisms.

Component 37244-96-5:

No data

Component 64742-95-6:

Readily biodegradable

Component 123-86-4:

No Data

Bioaccumulative potential:

Component 100-41-4:

Does not bioaccumulate

Component 1333-86-4:

Not expected to bioaccumulate.

Component 37244-96-5:

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 12 of 15

No data

Component 64742-95-6:

No Data

Component 123-86-4:

No Data

Mobility in soil:

Component 100-41-4:

Mobile; may contaminate groundwater

Component 37244-96-5:

No data

Component 64742-95-6:

No data

Component 123-86-4:

No data

Other Adverse Ecological Effects:

No information

Component 100-41-4:

Dissolved material evaporates rapidly - within a day from water or soil surfaces.

Component 37244-96-5:

Not expected to present an environmental hazard.

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 13 of 15

Component 64742-95-6:

Toxic to aquatic life with long lasting results.

13. Disposal Considerations

Waste Disposal Method:

Discharge, treatment or disposal is subject to national, state, or local laws. When a decision is made to discard this material as supplied, it meets RCRA's characteristic definition of ignitability. The toxicity characteristic (TC) has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Federal Regulations may apply to empty container. State and/or local regulations may be different.

Of the methods of disposal currently available, it is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: (1) recycle or rework, if feasible; (2) incinerate at an authorized facility; or (3) treat at an acceptable waste treatment facility.

Be sure to contact the appropriate government environmental agencies if further guidance is required.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

DOT (USA) Shipping Name: Not regulated by DOT, COMBUSTIBLE LIQUID*

UN/NA ID No: n/a

Hazard Class: n/a

Packing Group: n/a

*NOT REGULATED BY GROUND TRANSPORTATION IN NON-BULK PACKAGING (450L OR 119 GALLONS OR LESS) PER CFR 173.150 (f)(2).

IF SHIPPED BY AIR, VESSEL OR IN BULK THEN:

Shipping name: Paint

UN/NA ID No: UN1263

Hazard Class: 3

Packing Group: III

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 14 of 15

Environmental Hazards:
INFORMATION NOT AVAILABLE.

Marine Pollutant:
Components of this product do not appear on the list of Marine Pollutants (49CFR 172.101)

Special Precautions for User:
INFORMATION NOT AVAILABLE.

15. Regulatory Information

U.S. Federal Regulations:
TSCA: All components of this material are on the US TSCA 8(b) Inventory or are exempt from listing.

OSHA:
This product is hazardous under OSHA's Hazard Communication Std. Not regarded as a health hazard under current legislation.

CERCLA: SARA Hazard Category:
INFORMATION NOT AVAILABLE.

Section 313:
"*" Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

International Regulations:

Canadian WHMIS:
INFORMATION NOT AVAILABLE.

Canadian Environmental Protection Act (CEPA):
INFORMATION NOT AVAILABLE.

EINECS:
INFORMATION NOT AVAILABLE.

State Regulations:

"#" Indicates a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

"+" Indicates a Clean Air Act Hazardous Air Pollutant (HAP).

Volatile Organic Compounds:
COATING VOC content is being expressed as mass of VOC per unit volume of coating less water and exempt solvents, where applicable.
MATERIAL VOC content is the actual weight of VOC per unit volume.

16. Other Information

Date Revised: 11/03/21

Prepared By: Regulatory Compliance

Information Contact: Regulatory Compliance 413-592-4191 ext 106

Manufacturer Disclaimer:

SAFETY DATA SHEET

Eastern Chem-Lac

RANDOGRIP NAVY METAL PRIMER GRAY MIL-PRF-24667 TY 1, 2, & 4 PT A-PAIL

Date Printed: 2/8/2022

Page 15 of 15

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees, as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate.

However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. These data relate only to the specific material designated herein and do not relate to use in combination with any other material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

End of Material Safety Data Sheet